



Introduction – Methodology – Case Study – Conclusion and Future Work

Background



Swarm Performance



Area Surveillance

Application of MASs in Various Fields






Target Tracking



Background





Attack

System Model

- Consider a single-integrator MAS modelled by
- A consensus-seeking protocol^[3] is introduced as


$$x_{i}[k+1] = x_{i}[k] + u_{i}[k]$$

$$x_{i} = x_{i} = x_{i}[k] + u_{i}[k]$$

$$x_{i} = x_{i} = x_{i} = x_{i} = x_{i}$$

$$x_{i} = x_{i} = x_{i}$$

$$x_{$$



Agent 1 is subject to malicious attack

[3] W. Ren and Y. Cao, Distributed Coordination of Multi-Agent Networks: Emergent Problems, Models, and Issues. Springer, 2011.



Background

Definition 1 (Normal Agent). An agent is said to be normal if adopts the predetermined rule for state update.

Definition 2 (Malicious Agent). An agent is said to be malicious if it adopts some other function at some time step.

Challenges

- Resilient algorithm design
- Communication load
- Heterogeneity
- Time-varying networks
- •



Existing Studies

Attack Detection and Isolation Method^[1] Attack tolerant Method^[2]

- Detecting and isolating malicious agents
- Agents in the network are equipped with observers
- Massive data processing
- High network connectivity required

- Deleting malicious state values
- More lightweight with less computational complexity
- Less data processing
- Less prior information required

^[2] H. J. LeBlanc, H. Zhang, X. Koutsoukos, and S. Sundaram, "Resilient asymptotic consensus in robust networks," IEEE J. Sel. Areas Commun., vol. 31, no. 4, pp. 766–781, 2013.



^[1] I. Shames, A. M. Teixeira, H. Sandberg, and K. H. Johansson, "Distributed fault detection for interconnected second-order systems," Automatica, vol. 47, no. 12, pp. 2757–2764, 2011.

Resilient Consensus

Mean Subsequence Reduced (MSR) Algorithm

• Resilience: For each normal agent $i \in \mathcal{N}$, it holds $x_i[k] \in \mathcal{I}, \ \forall k \in \mathbb{Z}_{\geq 0}$, where

$$\mathcal{I} = \left[\min_{i \in \mathcal{N}} x_i[0], \max_{i \in \mathcal{N}} x_i[0]\right]$$

represents a safety interval.

• **(Exact) Consensus:** For each pair of normal agents $i, j \in \mathcal{N}$, it holds $\lim_{k \to \infty} \left| x_i[k] - x_j[k] \right| = 0, \quad \forall k \in \mathbb{Z}_{\geq 0}.$





1. Sorting





3. Updating



MSR Algorithm






1. Sorting

2. Deleting



3. Updating






$$[x_1[0], \dots, x_7[0]] = [10, 8, 6, 7, 4, -5, 6], f = 2$$

Agent 2:
$$x_2[0] = 8$$
 $x_j[0] = [10,6,7,-5]$

$$S = [-5, 6, 7, 8, 10]^{T}$$



$$S_{del} = [-5, 6, 7, 8, 10]^{T}, \quad \mathcal{R}_{i} [k] = \{4\}$$
3. Updating

$$x_{i}[k+1] = x_{i}[k] + \sum_{j \in \mathcal{R}_{i}[k]} a_{ij}[k] (x_{j}[k] - x_{i}[k])$$



MSR Algorithm

Event-based MSR (E-MSR) Algorithm^[4]









1. Sorting

2. Deleting

Require $x_j[k]$ at each time step

1. Sorting

2. Deleting









3. Updating

3. Updating

4. Checking

[4] Y. Wang and H. Ishii, "Resilient consensus through event-based communication," IEEE Trans. Control Netw. Syst., vol. 7, no. 1, pp. 471–482, 2020.



Static Event-Triggered Mechanism^[4]

The control protocol is modified as

$$x_{i}[k+1] = x_{i}[k] + \sum_{j \in \mathcal{R}_{i}[k]} a_{ij}[k] \left(\hat{x}_{j}[k] - x_{i}[k]\right)$$
Auxiliary variable

• The update of auxiliary variable depends on

$$\hat{x}_i[k+1] = \begin{cases} x_i[k+1], & \text{if } f_i[k] > 0, \\ \hat{x}_i[k], & \text{otherwise.} \end{cases}$$

The static event-triggered function (SETF) is designed as

$$f_i[k] = \left| x_i[k+1] - \hat{x}_i[k] \right| - \left(c_0 + c_1 e^{-\alpha k} \right)$$
Error term $\left| e_i[k] \right|$ Threshold




Illustration of the static event-triggered mechanism.

[4] Y. Wang and H. Ishii, "Resilient consensus through event-based communication," IEEE Trans. Control Netw. Syst., vol. 7, no. 1, pp. 471–482, 2020.



E-MSR Algorithm^[4]





1. Sorting







3. Updating

4. Checking

4. Agent *i* checks whether SETF triggers or not and sets $\hat{x}_i[k+1]$ as

$$\hat{x}_i[k+1] = \begin{cases} x_i[k+1], & \text{if SETF triggers,} \\ \hat{x}_i[k], & \text{otherwise.} \end{cases}$$

Shortcomings:

- Only bounded resilient consensus can be achieved due to the existence of constant term c_0 , i.e., $\lim_{k\to\infty} \left|x_i[k]-x_j[k]\right| \leq c, \quad \forall k\in\mathbb{Z}_{\geq 0}.$
- The threshold cannot dynamically adjust as the error term changes.

[4] Y. Wang and H. Ishii, "Resilient consensus through event-based communication," IEEE Trans. Control Netw. Syst., vol. 7, no. 1, pp. 471–482, 2020.



Dynamic Event-Triggered Mechanism

• The control protocol is also modified as

$$x_i[k+1] = x_i[k] + \sum_{j \in \mathcal{R}_i^{\text{in}}[k]} a_{ij}[k] (\hat{x}_j[k] - x_i[k])$$


• A dynamic variable $\delta_i[k]$ is introduced, whose state update follows

$$\delta_i[k+1] = (1-\theta_i)\delta_i[k] + \eta_i(\psi[k] - |e_i[k]|)$$

Always greater than zero and converges to zero.

• The dynamic event-triggered function (DETF) is designed as

$$f_i[k] = \left| e_i[k] \right| - \left(\psi[k] + \frac{\delta_i[k]}{\xi_i} \right)$$



Comparison between the static and dynamic event-triggered mechanism.



Dynamic Event-triggered Mean Subsequence Reduced (DE-MSR) Algorithm^[5]




1. Sorting





2. Deleting



$$\hat{x}_i[k+1] = \begin{cases} x_i[k+1], & \text{if DETF triggers,} \\ \hat{x}_i[k], & \text{otherwise.} \end{cases}$$



3&5. Updating



4. Checking

Agent *i* updates its interval dynamical variable according to


$$\delta_i[k+1] = (1-\theta_i)\delta_i[k] + \eta_i(\psi[k] - |e_i[k]|)$$

[5] Z. Liao, J. Shi, S. Wang, Y. Zhang, and Z. Sun, "Resilient consensus through dynamic event-triggered mechanism," IEEE Trans. Circuits Syst. II-Express Briefs, 2024, doi: 10.1109/TCSII.2024.3364524.



Comparative example between SETF and DETF

Communication topology



Simulation Setting

- Agent 1 is a malicious agent, whose motion follows $x_1[k] = 5 \times \sin(k/5) + 7$
- Initial state values of all agents are denoted as $[x_1[0], \dots, x_7[0]] = [7,7,6,8,-5,8,6]$
- SETF related parameters:

$$c_0 = 5 \times 10^{-4}, c_1 = 0.01, \alpha = 0.01$$

DETF related parameters:


$$\xi_i = 10, \eta_i = 0.6, \theta_i = 0.35, \delta_i[0] = 15, \psi[k] = e^{-\beta k}, \beta = 0.01$$

Purpose

- To validate the effectiveness of the proposed DE-MSR algorithm.
- To show the superiority of the DETF compared with the SETF.



Simulation Results





Introduction – Methodology – Case Study – **Conclusion and Future Work**

Conclusion

- Study the resilient consensus problem based on the dynamic event-triggered mechanism.
- Propose the DE-MSR algorithm to reduce communication overheads.
- Validate the effectiveness of the proposed method through numerical simulations.

Future Work

- MASs with disturbances generated from the external environment.
- More general and complex tasks (e.g., resilient distributed optimization).



